



C66

3-Round Liquid CARTRIDGE HOUSINGS

C66 3-Round Liquid Cartridge Housings give the versatility of choosing cartridges for the needed flow rates, chemical compatibility and particle retention. The C66 accommodates three elements in 20-, 30- or 40-inch lengths.

APPLICATIONS

- Commercial
- General Industrial


FEATURES

- Flow rates to 60 gpm
- Carbon or Stainless Steel construction
- Quick-swing closure with eye nuts
- Buna-N® lid seal
- 316 Stainless Steel cup and spring assemblies
- 150 PSI pressure rating
- Differential, drain, and vent ports available
- Adjustable support legs
- Two-part epoxy paint inside and outside on carbon steel
- 316 Stainless Steel center guide post
- Made to accept double open end cartridges (DOE) or 222 style with closed top cap*

*Note: Type of element top which will be used must be noted at the time of the housing order.

HOUSING OPTIONS

- Duplexing for continual flow during maintenance
- Higher pressure rating
- 226 o-ring
- Fin style top
- ASME Code U or UM




**Pentair
Industrial**

C66 3-Round Cartridge Housings

ORDERING INFORMATION


Custom configurations available; please contact Customer Service.




* Note: If double open end (DOE), it is only required once in the part number and will specify both top and base. Cartridges are not included but must be specified as to the type using when ordering the housing.

DIMENSIONS

Threaded (NPT) Type



Flange Type



Housing #	Cartridge Length (in.)	Conn. Size Options (in.)	# of Cartridges	DIMENSIONS (in.)						
				A	B	C	D	E	F	G
C66	20	1	3	6.6	24.5	22.3	6.0	4.1	5.2	23.5
		1.25 1.50	3	6.6	34.5	32.3	6.0	4.1	5.2	33.5
	40	2	3	6.6	44.5	42.3	6.0	4.1	5.2	43.5
		3								

All dimensions are approximate.



502 Indiana Avenue, Sheboygan, WI 53082-1047
 800.869.0325 574.278.7161 FAX 574.278.7115
 support@pentairindustrial.com www.pentairindustrial.com