

Liquid FILTER BAGS

Economical filtration for a wide array of applications. Highly controlled manufacturing procedures ensure consistent quality and no contamination. The unique bag designs provide added strength and avoids risk of bypass. Our filter bags will fit all industry-standard bag housings.

APPLICATIONS

- Automotive
- Commercial
- General Industrial
- Paints, Inks, Coatings
- Water

FEATURES

- Available medias range from 1 to 1500 microns
- Heavy-duty handle for easy installation and removal
- Wide array of media fibers to meet needed temperature and micron specifications
- Bag finish or covers available for strict migration requirements
- OEM replacement ring styles
- Multi-layered filtering capabilities for higher dirt-holding capacities and fewer change-outs
- Dimensions range from 4.12-inch diameter × 8-inch length thru 9-inch diameter × 32-inch length

REPLACEMENT BAGS AVAILABLE FOR:

American Felt™
Commercial™
Cuno®
Filter Specialists™ (FSI)
Filtration Systems™
GAF Filter Systems™
Plenty™
Ronnigen-Petter™
Rosedale™
Strainrite™

BAG SPECIFICATIONS

| Model No. | Bag Size | Length (inches) | Diameter (inches) | Surface Area (sq. ft.) |
|--------------|----------|-----------------|-------------------|------------------------|
| 44-6 | #3 | 8 | 4.12 | .5 |
| 44-12 | #4 | 14 | 4.12 | 1.0 |
| 66-12 | #7 | 15 | 5.62 | 1.3 |
| 66-18 | #8 | 21 | 5.62 | 2.0 |
| 66-30 | #9 | 32 | 5.62 | 3.4 |
| 88-15 | #1 | 16.5 | 7.06 | 2.0 |
| 88-15 | #1 inner | 14.5 | 5.75 | 1.6 |
| 88-30 | #2 | 32 | 7.06 | 4.4 |
| 88-30 | #2 inner | 30 | 5.75 | 3.6 |
| M88-30-OEM | #12 | 30 | 8.00 | 5.5 |
| Multi-Rounds | #2 | 32 | 7.06 | 4.4 |

MICRON RATINGS PERFORMANCE

| Fiber | Micron Rating | | | | | | | | | | | | | | Temp | | |
|---|---------------|---|----|----|----|----|----|-----|-----|-----|-----|-----|-----|-----|------|-----|-----------------|
| | 1 | 5 | 10 | 15 | 25 | 50 | 75 | 100 | 150 | 200 | 250 | 300 | 400 | 600 | | 800 | 1500 |
| Felt, Nomex (HT) | | • | • | • | • | • | • | • | | | | | | | | | 450°F (232.2°C) |
| Felt, Polyester (KE) | • | • | • | • | • | • | • | • | • | | | | | | | | 250°F (121.1°C) |
| Felt, Polypropylene (KO) | • | • | • | | • | • | • | | | | | | | | | | 200°F (93.3°C) |
| Monofilament Mesh, Nylon (NMO) | | • | • | | • | • | • | • | • | • | • | • | • | • | • | • | 250°F (121.1°C) |
| Monofilament, Polyester (KEMO) | | • | • | | • | • | • | • | • | • | • | • | • | • | • | • | 250°F (121.1°C) |
| Monofilament Mesh, Polypropylene (KOMO) | | | | | | | | | | | | • | • | • | • | • | 200°F (93.3°C) |
| Multifilament Mesh, Nylon (NM) | | | | | | | | | | • | | | | | | | 250°F (121.1°C) |
| Multifilament Mesh, Polyester (KEM)* | | | | | | | | | • | • | • | • | | • | • | • | 250°F (121.1°C) |
| Oil Removal (OR) | | | | | • | | | | | | | | | | | | 200°F (93.3°C) |

* Multifilament Polyester also available in 125, 1000 and 1500 microns.




**Pentair
Industrial**

Liquid Filter Bags

ORDERING INFORMATION

Custom configurations available; please contact Customer Service.



| SECTION 1 | SECTION 2 | SECTION 3 |
|---|---|--|
| Fibers | Micron Ratings Available for the Designated Fibers | Bag Finish or Cover (Over Felt Only) |
| KE = Felt, Polyester | KE = 1, 5, 10, 15, 25, 50, 75, 100, 200 | K = None |
| KO = Felt, Polypropylene | KO = 1, 5, 10, 25, 50, 100 | FF = Fiber-Free (Polyester Micron Fiber or Felt Only) |
| NMO = Monofilament Mesh, Nylon | NMO = 5, 10, 25, 50, 75, 100, 125, 150, 175, 200, 250, 300, 400, 600, 800 | G = Glazed Finish |
| KEM = Multifilament Mesh, Polyester | KEM = 75, 100, 125, 150, 200, 250, 300, 400, 800, 1500 | KEM = Polyester Multifilament Mesh Cover |
| OR = Oil Removal Material | OR = 25 | C = Spun-Bonded Nylon (Cerex®) |
| HT = Felt, Nomex (nylon) | HT = 5, 10, 25, 50, 100 | R = Spun-Bonded Polyester (Reemay®) |
| KOMO = Monofilament Mesh, Polypropylene | KOMO = 75, 100, 125, 150, 175, 200, 250, 300, 400 | NM = Nylon Multifilament Mesh Cover |
| NM = Multifilament Mesh, Nylon | NM = 150 | NMO = Nylon Monofilament Mesh Cover |
| | | A = Automotive |
| | | KOMO = Polypropylene Monofilament Mesh Cover |

* Multifilament Polyester also available in 125, 1000 and 1500 microns.

| SECTION 4 | | SECTION 5 |
|---|--|---|
| Size & Symbol with Useage and Bag Dimensions | | Ring Styles |
| 1 = Standard #1 Size Housings - Model 88-15 - 7.0625" dia. x 16.5" long | 8 = Standard #8 Size Housings - Model 66-18 - 5.625" dia. x 21" long | S = Carbon steel Ring |
| 1K = FSI #1 Size Housings - 7" dia. x 16.5" long | 9 = Standard #9 Size Housings - Model 66-30 - 5.625" dia. x 32" long | SS = Stainless Steel Ring |
| 2 = Standard #2 Size Housings - Model 88-30 - 7.0625" dia. x 32" long | 12 = Standard #12 Size Housings - Model M88-30-0EM - 8" dia. x 32" long | KO = Polypropylene Ring |
| 2K = FSI #2 Size Housings - 7" dia. x 32" long | CU1 = Cuno #1 Size Housings - Model PC1 - 9" dia. x 20" long | B = Stainless Steel Band on Commercial Bags |
| 3 = Standard #3 Size Housing - Model 44-6 - 4.125" dia. x 8" long | CU2 = Cuno #2 Size Housings - Model PC2 - 9" dia. x 30" long | K = FSI Style Flanged Plastic Top |
| 3K = FSI #3 Size Housings - 4.125" dia. x 8" long | RK1 = Ronningen Petter Fabric Basket Housings #1 Size - 8" dia. x 30" long | |
| 4 = Standard #4 Size Housing - Model 44-12 - 4.125" dia. x 14" long | RK2 = Ronningen Petter Fabric Basket Housings #2 Size - 8" dia. x 40" long | |
| 4K = FSI #4 Size Housings - 4.0625" dia. x 14" long | CO1 = Commercial Filters #1 Size Housings - 7.3125" x 17" long | |
| 7 = Standard #7 Size Housings - Model 66-12 - 5.625" dia. x 15" long | CO2 = Commercial Filters #2 Size Housings - 7.3125" dia. x 33" long | |



502 Indiana Avenue, Sheboygan, WI 53082-1047
 800.869.0325 574.278.7161 FAX 574.278.7115
 support@pentairindustrial.com www.pentairindustrial.com